

	Type	Ref. No.	Electrical (atRoomTemp.) Nominal Voltage (V)	Dimensions Diameter (mm)	Dimensions Height (mm)	Weight (g)	C.C.V. (TYP.)* +24°C(V)	C.C.V. (TYP.)* -10°C(V)
Low	SR416SW	337	1.55	4.8	1.65	0.11	1.35	1.10
Low	SR421SW	348	1.55	4.8	2.15	0.14	1.35	1.10
Low	SR512SW	335	1.55	5.8	1.25	0.15	1.45	1.10
Low	SR516SW	317	1.55	5.8	1.65	0.18	1.45	1.10
Low	SR521SW	379	1.55	5.8	2.15	0.23	1.45	1.10
Low	SR527SW	319	1.55	5.8	2.7	0.29	1.45	1.10
Low	SR616SW	321	1.55	6.8	1.65	0.25	1.45	1.10
Low	SR621SW	364	1.55	6.8	2.15	0.32	1.45	1.20
Low	SR626SW	377	1.55	6.8	2.6	0.39	1.45	1.20
Low	SR712SW	346	1.55	7.9	1.25	0.26	1.45	1.10
Low	SR714SW	341	1.55	7.9	1.45	0.29	1.45	1.20
Low	SR716SW	315	1.55	7.9	1.65	0.33	1.45	1.20
Low	SR721SW	362	1.55	7.9	2.1	0.42	1.45	1.20
Low	SR726SW	397	1.55	7.9	2.6	0.52	1.45	1.20
Low	SR731SW	329	1.55	7.9	3.1	0.56	1.45	1.20
Low	SR41SW	384	1.55	7.9	3.6	0.67	1.45	1.20
Low	SR912SW	-	1.55	9.5	1.25	0.40	1.45	1.20
Low	SR916SW	373	1.55	9.5	1.65	0.51	1.45	1.20
Low	SR920SW	371	1.55	9.5	2.05	0.6	1.45	1.20
Low	SR927SW	395	1.55	9.5	2.7	0.75	1.45	1.20
Low	SR936SW	394	1.55	9.5	3.6	1.1	1.45	1.20
Low	SR1120SW	381	1.55	11.6	2.05	0.93	1.45	1.20
Low	SR1130SW	390	1.55	11.6	3.05	1.29	1.45	1.20
Low	SR43SW	301	1.55	11.6	4.2	1.75	1.45	1.20
Low	SR44SW	303	1.55	11.6	5.4	2.2	1.45	1.20
High	SR626W	376	1.55	6.8	2.6	0.39	1.35	0.95
High	SR721W	361	1.55	7.9	2.1	0.41	1.35	1.05
High	SR726W	396	1.55	7.9	2.6	0.52	1.35	1.05
High	SR41W	392	1.55	7.9	3.6	0.67	1.35	1.05
High	SR920W	370	1.55	9.5	2.05	0.6	1.4	1.10
High	SR927W	399	1.55	9.5	2.7	0.75	1.4	1.10
High	SR1120W	391	1.55	11.6	2.05	0.93	1.4	1.20
High	SR1130W	389	1.55	11.6	3.05	1.29	1.4	1.20
High	SR43W	386	1.55	11.6	4.2	1.75	1.45	1.20
High	SR44W	357	1.55	11.6	5.4	2.2	1.45	1.20